



CODEMARK™

CERTIFICATE OF CONFORMITY

This is to certify that

HomeGuard Precision Termite Management System



Product Description

- HomeGuard TMB**, 0.2mm sheet Polyethylene with Bifenthrin incorporated in it. Used in full underslab termite management installations and critical joints.
- HomeGuard DPC**, 0.5mm sheet Polyethylene with Bifenthrin incorporated in it. Used in perimeter (cavity) termite management installations.
- HomeGuard Blue**, 0.25mm sheet Polyethylene with Bifenthrin incorporated in it. Used in perimeter (cavity) termite management installations.
- HomeGuard Collars**, rigid Polyethylene collars with Bifenthrin incorporated in them. Used as a termite management system for penetrations.

Product Purpose or Use

A physical underslab, perimeter and penetration system to deter concealed entry by subterranean termites into a building.

Certificate Holder

FMC Australasia Pty Ltd
ABN 45 095 326 891
6/9 Archimedes Place
Murrarie QLD 4172

CodeMark Certification Body

SAI Global Certification Services Pty Limited
(ACN 108 716 669) Trading as "SAI Global"
JAS-ANZ Accreditation No. Z1440295AS
Address: 286 Sussex Street, Sydney, NSW 2000
Website: www.saiglobal.com

Complies with the Building Code of Australia (BCA):

- Volume One: BP1.1 and BP1.2 (*limited only to actions by subterranean termites*)
- Volume Two: P2.1 (*limited only to actions by subterranean termites*)
- State Additions: Volume Two: QLD P2.1.1 (*limited only to actions by subterranean termites*)

Subject to the following conditions and limitations:

- The FMC HomeGuard Precision Termite Management System is to be installed by licensed installers trained and approved by FMC Australasia Pty Ltd.
- The FMC HomeGuard Precision Termite Management System is to be installed in accordance with the version 2 of the FMC HomeGuard installation manual dated June 2006.
- The FMC HomeGuard installation manual shall be read in conjunction with the Addendum volume issued 22nd June 2007 and the HomeGuard Blue Installation Supplement dated 29th November 2007.
- The HomeGuard DPC and HomeGuard Blue when used across a perimeter cavity must finish at least 75mm above the surrounding finished ground level.
- Penetrations of a different size to the preformed HomeGuard collar are to be protected using the HomeGuard sheet collars made as described in the installation manual
- The HomeGuard collars are not to be glued to any of the penetrations that they protect as described in the installation manual.
- The concrete slab must be constructed in accordance with the requirements of AS 2870-1996 Residential slabs and footings - Construction (*as amended up to and including Amdt 4, May 2003*)
- Inspections are undertaken annually in accordance with the FMC HomeGuard installation manual to determine that no bridging or breaching of the barrier has occurred.



Alex Ezrakhovich
General Manager Certification
For and on behalf of SAI Global

29/11/2007

**Reissue
Date**

19/07/2007

**Original
Date of Issue**

18/07/2010

Date of Expiry

SAIG-07-CM20003

Certificate Number

- This Certificate of Conformity is issued under arrangement with JAS-ANZ. The ABCB does not in any way warrant or represent that the Product the subject of this Certificate of Conformity conforms with the BCA, nor accepts any liability arising out of the use of the Product.
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, www.abcb.gov.au.